

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently amended) A connection assembly for transferring a fluid, particularly a fluid containing active products, from a reservoir to a medical delivery device comprising:

a first connection element associated with the reservoir and comprising first retaining means[.,,];

a second connection element associated with the medical delivery device and comprising second retaining means capable of cooperating with the first retaining means to form an irreversible connection between the two elements[.,,]; and

a weakened area in at least one of the first and second connection elements, the at least one connection element breakable at the weakened area in response to a shear force applied thereto,

wherein the first and second retaining means are arranged such that they cooperate with each other by clipping during a single translation movement of one connection element with respect to the other to make the connection irreversible, ~~and wherein at least one of the connection elements comprises means capable of making it breakable.~~

2. (Previously Presented) The connection assembly according to claim 1, wherein either the first or second retaining means comprises at least one elastically deformable tab and the other retaining means comprises at least one lip capable of cooperating with the tab.

3. (Previously Presented) The connection assembly according to claim 2, wherein either the first or second retaining means comprises two tabs located on opposite sides of the first or second connection element.

4. (Previously Presented) The connection assembly according to claim 1, wherein either the first or second retaining means comprises at least one recess and the other retaining means comprises at least one lip capable of cooperating with the recess.
5. (Currently amended) The connection assembly according to claim 2 ~~any of claims 2 to 4~~, wherein the lip is elastically deformable.
6. (Previously Presented) The connection assembly according to any of claims 1 to 4, wherein either the first or second connection element comprises a male part and the other connection element comprises a female part with a shape complementary to the male part and capable of cooperating with the male part so as to make the connection leak tight.
7. (Previously Presented) The connection assembly according to claim 6, wherein the male and female parts are Luer cones with a taper of about 6%.
8. (Previously Presented) The connection assembly according to claim 6, wherein the male part is an essentially tubular shaped perforator.
9. (Currently amended) The connection assembly according to claim 1 ~~one of claims 1 or 4~~ wherein the assembly also comprises non-return means capable of preventing fluid from coming out after injection .
10. (Previously Presented) The connection assembly according to claim 7, wherein the first or second connection element is irreversibly connected to standard connectors before an irreversible connection is made with the other element.
11. (Previously Presented) The connection assembly according to claim 8, wherein the second connection element makes use of the perforator to make reversible to make reversible

connections onto receptacles before an irreversible connection is made with the first connection element.

12. (Currently amended) A connection element for transfer of fluid, particularly fluid containing active products, from a reservoir to a medical delivery device, comprising:

a first retaining means, wherein the first retaining means are arranged such that they cooperate with a second retaining means in another connection element by clipping during a single translation movement between the two connection elements to make an irreversible connection between the two connection elements; and

a weakened area ~~means adapted to break and~~ situated on at least one of the connection elements adapted to break upon application of a shear force.

13. (New) The connection assembly according to claim 1, wherein the weakened area comprises a notch.

14. (New) The connection assembly according to claim 13, wherein the notch is continuous around an outer periphery of the at least one connection element.

15. (New) The connection assembly according to claim 3, wherein the lip is elastically deformable.

16. (New) The connection assembly according to claim 4, wherein the lip is elastically deformable.

17. (New) The connection assembly according to claim 4, wherein the assembly also comprises non-return means capable of preventing fluid from coming out after injection.

18. (New) A method for forming a frangible connection for transferring a fluid, particularly a fluid containing active products, between a reservoir and a medical delivery device comprising the steps of:

(i) translating a first connection element associated with the reservoir and having first retaining means relative to a second connection element associated with the medical delivery device and having a second retaining means;

(ii) irreversibly connecting together the translated first and second connection elements through cooperation of the first and second retaining means;

(iii) transferring a fluid between the reservoir and the medical delivery device through the irreversibly connected first and second connection elements; and

(iv) applying a shear force to at least one of the irreversibly connected first and second connection elements causing at least one of the first and second connection elements to break at a weakened area provided therein.

19. (New) The method of claim 18, wherein the at least one of the first and second connection elements broken by application of the shear force is unable to form another irreversible connection with another one of the first and second connection elements.

20. (New) The method of claim 18, wherein the weakened area comprises a notch.

21. (New) The method of claim 20, wherein the notch is continuous around an outer periphery of the at least one connection element.